
Fixed Exchangers
Water Heaters
SMART 2 HP



Glass lined water heater with fixed double heat exchanger for Heat pumps – SMART HP 2

The HP 2 range consists of water heaters for the production of domestic hot water with a double fixed heat exchangers, one simple and one with double spiral with a large surface, to be coupled with a heat pump together with additional sources (solar, gas water heater). The heaters are available in the capacities of 300 and 500 l and are insulated with very thick high density rigid polyurethane, externally covered with PVC and provided with a magnesium anode to protect against galvanic currents and an inspection flange for easy access during the inspection and maintenance phase.

Material: S 235 JR carbon steel

Treatment for internal protection: Food grade inorganic glass lining according to DIN 4753.3

WRAS APPROVED MATERIAL

Insulation

Capacity (l)	Type
from 300 to 1000	Highly rigid polyurethane foam

Operational limits


Cap. l	Storage		Primary circuit	
	max. temperature	max. pressure	max. temperature	max. pressure
from 300 to 1000	95°C	10 bar	110°C	12 bar

Supplied accessories: Safety valve and thermometer, magnesium sacrificial anode.

Standard accessories: see pag 294



TESTED



Capacity l	Code	Price	Energy label	Vertical Packaging	
				Dimensions cm	Weight kg
300	819060307X		B	70X70X155	129
500	819060308X		C	80X80X180	182
750	819060309X		C	95X95X185	264
1000	819060310X		C	105X105X210	314




Integration with AQUAFAST


See page 212

Glass lined water heater with fixed double heat exchanger for Heat pumps – SMART HP 2

300 ≤ cap. ≤ 500



750 ≤ cap. ≤ 1.000



Couplings legend

A1	DHW inlet
A2	DHW outlet
C1	Anode
E1	Probe / Thermometer
E2	Probe / Thermometer
E3	Probe / Thermometer
E4	Probe / Thermometer
F	Recirculation
I	Electrical resistor
K1	Auxiliary
K2	Auxiliary
K3	Auxiliary
N1	Lower exchanger outlet
N2	Lower exchanger inlet
N3	Upper exchanger outlet
N4	Upper exchanger inlet
Q1	Inspection hole
S1	Lower exchanger
S2	Upper exchanger

Couplings chart

Cap. l	A1 inch	A2 inch	C1 inch	E1 inch	E2 inch	E3 inch	E4 inch	F inch	I inch	K1 inch	K2 inch	K3 inch	N1 inch	N2 inch	N3 inch	N4 inch	Q1 (Øext/Øint) mm
300	1"	1"	1"1/4	1/2"	1/2"	1/2"	1/2"	1"	1"1/2	-	1"1/4	1"1/4	1"1/4	1"1/4	1"1/4	1"1/4	Ø180/Ø120
500	1"	1"	1"1/4	1/2"	1/2"	1/2"	1/2"	1"	1"1/2	-	1"1/4	1"1/4	1"1/4	1"1/4	1"1/4	1"1/4	Ø180/Ø120
750	1"1/2	1"1/2	1"1/4	1/2"	1/2"	1/2"	1/2"	1"	1"1/2	1"1/2	1"1/4	1"1/4	1"1/4	1"1/4	1"1/4	1"1/4	Ø180/Ø120
1000	1"1/2	1"1/2	1"1/4	1/2"	1/2"	1/2"	1/2"	1"	1"1/2	1"1/2	1"1/4	1"1/4	1"1/4	1"1/4	1"1/4	1"1/4	Ø180/Ø120

Size chart

Cap. l	Øe mm	Ht mm	R* mm	A1 mm	A2 mm	C1 mm	E1 mm	E2 mm	E3 mm	E4 mm	F mm	I mm	K1 mm	K2 mm	K3 mm	N1 mm	N2 mm	N3 mm	N4 mm	Q1** mm
300	660	1380	1530	130	1260	1380	355	945	1145	545	795	530	-	245	1085	245	465	595	1145	345
500	760	1650	1820	135	1515	1650	410	890	1350	600	1010	600	-	300	1140	300	520	670	1310	370
750	910	1675	1910	170	1540	1400	480	930	1400	650	1130	650	1675	330	1170	330	610	710	1320	350
1000	1010	1965	2210	190	1810	1670	500	945	1670	630	1150	680	1965	350	1190	350	635	735	1390	360

R*: reversal quota

Q1**: Height from inspection hole center to the ground


Technical information for SMART HP 2 series

		DHW production TiACS = 10°C			Exchanger		
Capacity	Ti	TuACS= 45°C		Ta = 50°C TuACS = 45°C	Upper exchanger surface	Lower exchanger surface	Nominal flow
l	°C	l/h (a)	kW (b)	l/10 min. (e)	m²	m²	mc/h
300	50	553	22,5	435	2,7	0,98	1,6
	80	1501	61,1	593			2,6
500	50	860	35	715	4,1	1,1	1,5
	80	2334	95	960			4,1
750	50	1380	52	920	4,9	2,2	3
	80	2800	115	1170			4,1
1000	50	1580	62	1080	5,5	2,5	3
	80	3000	135	1310			4,1

- a continuous DHW flow with TuDHW= 45°C
- e amount of DHW at 45°C in the first 10 min. with a storage temperature of 50°C
- Exchanger capacity: 6,40 L/m²


Key

1	Fiorini DHW storage tank
2	Magnesium anode
3	Heat pump
4	Solar thermal return group
5	Cold water bacteriostatic filter
6	DHW recirculation pump
7	Thermostatic DHW mixer
8	Fiorini solar panel
9	Safety group



Technical information for SMART HP 2 series

Pressure loss fixed heat exchanger





Download additional content

go.fiorinigroup.it/eng/content

fiorini

Fiorini Industries S.r.l.
Ph. +39 0543 723197 – Fax +39 0543 720413
Via Zampeschi 119 – 47122 Forlì (FC) – Italy
www.fiorini-industries.com