Thermal Solar Systems
H2000



H2000 - High efficiency flat plate solar panels with aluminium tank

H2000 high performance solar collector – 2 m² with an aluminium frame for vertical and horizontal installation

The new solar collector is made of profiles in high quality anticorrosive aluminium (Al Mg). It is endowed with a closing system with integrated perimeter gasket in vulcanized EPDM, and it is resistant to temperature swings and UV rays. It consists of a solar glass with antireflex safety, high transparency, a low iron content and insulation in qualitative mineral wool without formaldehyde and adhesives. The absorber is covered in highly selective vacuum aluminium and the product is endowed with connections. The collector is suitable for installation on the roof, for integration into the roof or for positioning on a structure. Performance and quality tested.



Features

- ✔ Unique and intelligent design
- ✔ Unbeatable price/quality ratio
- ✔ Precise manufacturing: construction on a motorized product line
- ✔ Intelligent fixing system: reduced installation time
- ✔ Several installation possibilities: up to 6 connected collectors, on tile, flat roofs...

	H2000 Vertical	
Gross surface	**code**	**price**
2 m²	821120058X	

Available models	
Article	**External dimensions**
H2000	1730 x 1170 x 83 mm

CHECK UPDATED PRICE LIST

go.fiorinigroup.it/pr

	Set for coupling collectors H2000/H2500	
	code	**price**
base	843070274X	
joint	843070275X	
expansion	843070277X	
horizontal joint	843070276X	

CHECK UPDATED PRICE LIST

go.fiorinigroup.it/pr

Connection options

Parallel connection



Max 6 collectors

Series connection



Based on pressure drop

Combined connection




Based on pressure drop

H2000 - High efficiency flat plate solar panels with aluminium tank

Technical information	
Gross surface (m^2)	2,02
Exposed surface (m^2)	1,84
Net surface (m^2)	1,84
Capacity (l)	1,56
Flow	high flow/low flow
Glass thickness	3,2 mm
Glass transmission coefficient	91%
Thickness of insulation	40 mm piano
Absorber	covered in highly selective vacuum aluminium
Absorption	95%
Emission	5%
Connections	4 x 22 mm
Operating pressure	10 bar
Testing pressure	15 bar
Max temperature	192°C
Weight	35 kg
Certificates	EN 12975 + Keymark
Warranty	10 years (glass not included)


Efficiency coefficient	Opening	Absorber
η_0	0,814	0,814
a_1	4,061	4,061
a_2	0,013	0,013



Assembly



On the roof
Horizontal, vertical
Fixing kit, frames and accessories



Supported
Frame for horizontal or vertical structure



Download additional content

go.fiorinigroup.it/eng/content

fiorini

Fiorini Industries S.r.l.
Ph. +39 0543 723197 – Fax +39 0543 720413
Via Zampeschi 119 – 47122 Forlì (FC) – Italy
www.fiorini-industries.com