
Removable Exchangers Water Heaters



fiorini

CHECK UPDATED PRICE LIST

go.fiorinigroup.it/pr

Water heater with tube heat exchanger – BOIL

The BOIL range consists of water heaters with a tube heat exchanger for the production of domestic hot water. There are several capacities, from 200 up to 5000 litres. They are equipped, depending on the capacity, with insulation (see chart below), an external cover in PVC and a magnesium anode for the protection against galvanic currents.



TESTED

Materials

The boilers are made from high quality materials such as:

- Tank: carbon steel S 235 JR
- Tube heat exchanger: galvanized stainless steel AISI 304
- Exchanger head: galvanized carbon steel S 235 JR

Internal protective treatment

- up to 1000 litres inorganic **glass lining**, according to DIN 4753.3
- from 1500 litres **Bluetech enamelling** with thermosetting resins, suitable for DHW

WRAS APPROVED MATERIAL

Insulation

Capacity (l)	Type
from 200 to 1000	Highly rigid polyurethane foam
from 1500	Polyester Fiber


Operational limits

	Storage		Primary circuit	
Capacity l	max. temperature	max. pressure	max. temperature	max. pressure
up to 1000	95°C	10 bar	110°C	12 bar
from 1500	80°C	6 bar	110°C	12 bar

Supplied accessories: Safety valve and thermometer for sizes up to 1000 l, magnesium sacrificial anode for all sizes.

Standard accessories: see pag 294

Special versions: see pag 296




Capacity l	Code	Price	Energy label	Vertical Packaging Dimensions cm	Vertical Packaging Weight kg
200	818060081X		A	75X75X125	84
300	818060082X		A	75x75x150	96
500	818060083X		B	85x85x180	136
750	818060084X		C	100x100x180	221
1000	818060085X		C	105x105x210	269
1500	818080375X		C	130x130x245	289
2000	818080361X		C	140x140x275	368
2500	818080362X			145x145x280	410
3000	818080363X			150x150x300	459
4000	818080364X			165x165x310	638
5000	818080365X			185x185x315	738




Integration with AQUAFAST

See page 212


Water heater
with tube heat exchanger – BOIL




200 ≤ cap. ≤ 1.000



1.500 ≤ cap. ≤ 5.000





Couplings legend

A1	DHW inlet
A2	DHW outlet
C1	Anode
C2	Anode
D	Drain
E1	Probe / Thermometer
E2	Probe / Thermometer
E3	Probe / Thermometer
F	Recirculation
I	Electrical resistor
K1	Auxiliary
K2	Auxiliary
K3	Auxiliary
K4	Auxiliary
N1	Lower exchanger outlet
N2	Lower exchanger inlet
Q1	Inspection hole
S1	Lower exchanger

Couplings chart

Cap. l	A1 inch	A2 inch	C1 inch	D inch	E1 inch	E2 inch	E3 inch	F inch	I inch	K1 inch	K2 inch	K3 inch	K4 inch	N1 inch	N2 inch	Q1 (Øext/Øint) mm
200	1"1/4	1"1/4	1"1/4	-	1/2"	1/2"	-	1"1/4	1"1/2	1"1/4	1"1/4	1"1/4	1"1/4	1"	1"	Ø300/Ø220
300	1"1/4	1"1/4	1"1/4	-	1/2"	1/2"	-	1"1/4	1"1/2	1"1/4	1"1/4	1"1/4	1"1/4	1"	1"	Ø300/Ø220
500	1"1/4	1"1/4	1"1/4	-	1/2"	1/2"	-	1"1/4	1"1/2	1"1/4	1"1/4	1"1/4	1"1/4	1"	1"	Ø300/Ø220
750	1"1/4	1"1/4	1"1/4	-	1/2"	1/2"	-	1"1/4	1"1/2	1"1/4	1"1/4	1"1/4	1"1/4	2"	2"	Ø380/Ø300
1000	1"1/4	1"1/4	1"1/4	-	1/2"	1/2"	-	1"1/4	1"1/2	1"1/4	1"1/4	1"1/4	1"1/4	2"	2"	Ø380/Ø300
1500	2"	2"	1"1/4	1"1/4	1/2"	1/2"	1/2"	1"1/4	1"1/2	1"1/4	1"1/4	1"1/4	-	2"	2"	Ø380/Ø300
2000	2"	2"	1"1/4	1"1/4	1/2"	1/2"	1/2"	1"1/4	1"1/2	1"1/4	1"1/4	1"1/4	-	2"	2"	Ø430/Ø350
2500	2"1/2	2"1/2	1"1/4	1"1/4	1/2"	1/2"	1/2"	1"1/4	1"1/2	1"1/4	1"1/4	1"1/4	-	2"	2"	Ø430/Ø350
3000	3"	3"	1"1/4	1"1/4	1/2"	1/2"	1/2"	1"1/4	1"1/2	1"1/4	1"1/4	1"1/4	-	2"	2"	Ø430/Ø350
4000	3"	3"	1"1/4	1"1/4	1/2"	1/2"	1/2"	1"1/4	1"1/2	1"1/4	1"1/4	1"1/4	-	2"	2"	Ø430/Ø350
5000	3"	3"	1"1/4	1"1/4	1/2"	1/2"	1/2"	1"1/4	1"1/2	1"1/4	1"1/4	1"1/4	-	2"	2"	Ø430/Ø350

Size chart

Cap. l	Øe mm	Ht mm	R* mm	A1 mm	C1 mm	D mm	E1 mm	E2 mm	E3 mm	F mm	I mm	K1 mm	K2 mm	K3 mm	K4 mm	N1 mm	N2 mm	Q1** mm
200	710	1105	1315	150	885	-	295	885	-	295	445	150	595	990	495	285	405	345
300	710	1355	1530	150	1135	-	445	1135	-	295	595	295	795	1135	495	295	415	355
500	810	1635	1825	145	1390	-	460	1390	-	310	610	310	1150	1390	510	310	430	370
750	950	1675	1925	180	1410	-	480	1410	-	330	650	330	1170	1410	530	358	503	430
1000	1010	1965	2210	200	1680	-	500	1680	-	350	670	350	1190	1680	550	378	523	450
1500	1250	2280	2600	500	1810	165	805	1810	1515	805	1215	500	1100	1340	-	5287	673	600
2000	1350	2600	2930	505	2115	155	805	2115	1805	805	1505	505	1105	1345	-	525	715	620
2500	1400	2655	3000	565	2150	175	865	2150	1850	850	1550	565	1165	1405	-	585	775	680
3000	1450	2870	3215	575	2350	180	800	2350	2050	850	1750	575	1050	1415	-	595	785	690
4000	1600	2940	3350	600	2380	160	900	2380	2080	870	1780	600	1200	1440	-	620	810	715
5000	1800	2980	3480	610	2385	140	910	2385	2085	885	1785	610	1210	1450	-	630	820	725

R*: reversal quota

Q1**: Height from inspection hole center to the ground

CHECK UPDATED PRICE LIST

go.fiorinigroup.it/pr

Stainless steel water heater with tube heat exchanger - BOIL INOX

The BOIL INOX range consists of water heaters with tube heat exchanger for the production of domestic hot water. They are available in several capacities, from 200 up to 5000 litres and equipped with Polyester Fiber insulation, external cover in PVC and a magnesium anode for protection against galvanic currents.



TESTED

Materials

The boilers are made from high quality materials such as:

- Tank: AISI 316 stainless steel
- Tube heat exchanger: AISI 316 stainless steel
- Exchanger head: galvanized carbon steel S235 JR

Treatment for internal protection: Pickling and passivation

Insulation

Capacity (l)	Type
from 200 to 5000	Polyester Fiber


Operational limits

Storage		Primary circuit	
max. temperature	max. pressure	max. temperature	max. pressure
95°C	6 bar	110°C	12 bar

Supplied accessories: Magnesium sacrificial anode for all sizes.

Standard accessories: see pag 294

Special versions: see pag 296



Capacity l	Code	Price	Energy label	Vertical Packaging Dimensions cm
200	818040113X		B	70x70x143
300	818040114X		B	80x80x160
500	818040115X		C	90x90x195
750	818040116X		C	100x100x200
1000	818040117X		C	110x110x230
1500	818040118X		C	130x130x240
2000	818040119X		C	150x150x250
2500	818040120X			150x150x280
3000	818040121X			150x150x300
4000	818040122X			170x170x305
5000	818040123X			190x190x310




Integration with AQUAFAST


See page 212

Stainless steel water heater with tube heat exchanger - BOIL INOX

200 ≤ cap. ≤ 300



500 ≤ cap. ≤ 5000



Couplings legend

A1	DHW inlet
A2	DHW outlet
C1	Anode
D	Drain
E1	Probe / Thermometer
E2	Probe / Thermometer
F	Recirculation
I	Electrical resistor
K1	Auxiliary
K2	Auxiliary
K3	Auxiliary
N1	Lower exchanger outlet
N2	Lower exchanger inlet
Q1	Inspection hole
S1	Lower exchanger

Couplings chart

Cap. l	A1 inch	A2 inch	C1 inch	D inch	E1 inch	E2 inch	F inch	I inch	K1 inch	K2 inch	K3 inch	N1 inch	N2 inch	Q1 (Øext/Øint) mm
200	1"1/4	1"1/4	1"1/4	1"1/4	1/2"	1/2"	1"1/4	1"1/2	1"1/4	1"1/4	-	1"	1"	Ø300/Ø220
300	1"1/4	1"1/4	1"1/4	1"1/4	1/2"	1/2"	1"1/4	1"1/2	1"1/4	1"1/4	-	1"	1"	Ø300/Ø220
500	1"1/4	1"1/4	1"1/4	1"1/4	1/2"	1/2"	1"1/4	1"1/2	1"1/4	1"1/4	1"1/4	1"	1"	Ø300/Ø220
750	1"1/2	1"1/2	1"1/4	1"1/4	1/2"	1/2"	1"1/4	1"1/2	1"1/4	1"1/4	1"1/4	2"	2"	Ø380/Ø300
1000	1"1/2	1"1/2	1"1/4	1"1/4	1/2"	1/2"	1"1/4	1"1/2	1"1/4	1"1/4	1"1/4	2"	2"	Ø380/Ø300
1500	1"1/2	1"1/2	1"1/4	1"1/4	1/2"	1/2"	1"1/4	1"1/2	1"1/4	1"1/4	1"1/4	2"	2"	Ø380/Ø300
2000	2"	2"	1"1/4	1"1/4	1/2"	1/2"	1"1/4	1"1/2	1"1/4	1"1/4	1"1/4	2"	2"	Ø430/Ø350
2500	2"1/2	2"1/2	1"1/4	1"1/4	1/2"	1/2"	1"1/4	1"1/2	1"1/4	1"1/4	1"1/4	2"	2"	Ø430/Ø350
3000	3"	3"	1"1/4	1"1/4	1/2"	1/2"	1"1/4	1"1/2	1"1/4	1"1/4	1"1/4	2"	2"	Ø430/Ø350
4000	3"	3"	1"1/4	1"1/4	1/2"	1/2"	1"1/4	1"1/2	1"1/4	1"1/4	1"1/4	2"	2"	Ø430/Ø350
5000	3"	3"	1"1/4	1"1/4	1/2"	1/2"	1"1/4	1"1/2	1"1/4	1"1/4	1"1/4	2"	2"	Ø430/Ø350

Size chart


Cap. l	Øe mm	Ht mm	R* mm	A1 mm	C1 mm	E1 mm	E2 mm	F mm	I mm	K1 mm	K2 mm	K3 mm	N1 mm	N2 mm	Q1** mm
200	650	1410	1535	295	1135	595	1135	425	540	295	915	-	305	425	365
300	750	1490	1650	335	1175	635	1175	465	605	335	935	-	345	465	405
500	850	1770	1945	350	1420	650	1420	650	935	350	950	1190	360	480	420
750	990	1810	2045	370	1440	670	1440	700	1150	370	990	1210	407,5	552,5	480
1000	1050	2100	2330	390	1710	690	1710	745	1150	390	990	1230	427,5	572,5	500
1500	1250	2235	2555	490	1800	795	1800	795	1205	490	1090	1330	517,5	662,5	590
2000	1450	2315	2725	525	1835	830	1835	830	1240	525	1125	1365	555	745	650
2500	1400	2640	2895	560	2145	860	2145	845	1545	560	1160	1400	575	765	670
3000	1450	2850	3155	565	2340	790	2340	840	1740	565	1040	1405	585	775	680
4000	1600	2920	3295	590	2370	890	2370	860	1770	590	1190	1430	610	800	705
5000	1800	2960	3425	600	2375	900	2375	875	1775	600	1200	1440	620	810	715

R*: reversal quota

Q1**: Height from inspection hole center to the ground

Technical information for BOIL and BOIL INOX series


		DHW production TiDHW = 10°C						Exchanger		
Capacity	Ti	TuDHW= 45°C		TuDHW = 60°C		Ta = 50°C TuDHW = 45°C	Ta = 60°C TuDHW = 45°C	Surface area	Capacity	Nominal flow
l	°C	l/h (a)	kW (b)	l/h (c)	kW (d)	l/10 min. (e)	l/10 min. (f)	m²	l	mc/h
200	70	241	9,8	119	4,9	258	315	0,5	2	0,5
	80	300	12,2	169	6,9	266	323			0,6
	90	362	14,7	214	8,7	273	330			0,7
300	70	364	14,8	181	7,4	384	470	0,75	2,8	0,7
	80	453	18,4	252	10,3	395	480			0,8
	90	544	22,1	322	13,1	405	491			1
500	70	482	19,6	240	9,8	620	763	1	3,6	0,9
	80	602	24,5	336	13,7	632	775			1,1
	90	580	23,6	343	14	644	787			1,1
750	70	723	29,4	358	14,6	983	1212	1,5	5,9	1,3
	80	902	36,7	506	20,6	1001	1229			1,6
	90	1084	44,1	642	26,2	1018	1247			1,9
1000	70	964	39,2	480	19,6	1224	1510	2	7,2	1,7
	80	1204	49	675	27,5	1245	1531			2,2
	90	1445	58,8	857	34,9	1266	1552			2,6
1500	70	1445	58,8	728	29,7	1837	2266	3	10,9	2,6
	80	1806	73,5	1020	41,6	1869	2297			3,2
	90	2168	88,2	1292	52,6	1899	2328			3,8
2000	70	1927	78,4	976	39,8	2421	2992	4	14,7	3,4
	80	2408	98	1368	55,7	2454	3026			4,3
	90	2890	117,6	1731	70,5	2488	3059			5,1
2500	70	2408	98	1232	50,2	3014	3728	5	18,5	4,3
	80	3010	122,5	1722	70,1	3053	3767			5,3
	90	3612	147	2178	88,7	3091	3805			6,4
3000	70	2890	117,6	1478	60,2	3577	4434	6	22	5,1
	80	3612	147	2066	84,1	3614	4471			6,4
	90	4335	176,4	2613	106,4	3650	4507			7,6
4000	70	3853	156,8	2020	82,3	4775	5918	8	30,1	6,8
	80	4816	196	2802	114,1	4824	5967			8,5
	90	5780	235,2	3530	143,7	4872	6015			10,2
5000	70	4816	196	2978	121,2	5938	7366	10	36,4	8,5
	80	6020	245	4099	166,9	5990	7419			10,6
	90	7224	294	5138	209,2	6042	7470			12,7




- a continuous DHW flow with TuDHW= 45°C
- b exchanger power with TuDHW=45°C
  c continuous DHW flow with TuDHW= 60°C
- d exchanger power with TuDHW=60°C
- e amount of DHW at 45°C in the first 10 min. with a storage temperature of 50°C
- f amount of DHW at 45°C in the first 10 min. with a storage temperature of 60°C
- Exchanger capacity: 6,40 L/m²

Technical information for BOIL and BOIL INOX series

Water only



Steam only



Couplings legend


D	Drain
N1	Exchanger inlet/outlet
N2	Exchanger inlet/outlet
T	Vent
1	Gasket without cross-beam
2	Bundle tube heat exchangers
3	Gasket with cross-beam
4	Head


Technical information tube heat exchanger

Surf. m²	Power* kW	Lt mm	Øext mm	Øhe mm	N1 inch	N2 inch	T, D inch	Z1 mm	Z2 mm	n° holes	Vol. l	dp mca
0,5	12,2	460	300	166	1"	1"	3/8"	120	262	16	1,84	0,65
0,75	18,4	445	300	202	1"	1"	3/8"	120	262	16	2,44	0,65
1	24,5	475	300	202	1"	1"	3/8"	120	262	16	3,23	0,7
1,5	36,7	600	380	270	2"	2"	3/8"	145	345	19	5,36	0,75
2	49	600	380	270	2"	2"	3/8"	145	345	19	6,51	0,8
3	73,5	720	380	278	2"	2"	3/8"	145	345	19	9,8	0,9
4	98	750	430	316	2"	2"	3/8"	190	395	22	13,2	1
5	122,5	780	430	324	2"	2"	3/8"	190	395	22	16,68	1,1
6	147	895	430	324	2"	2"	3/8"	190	395	22	19,2	1,2
8	196	1250	430	324	2"	2"	3/8"	190	395	22	27	1,3
10	245	1510	430	324	2"	2"	3/8"	190	395	22	32,7	1,4


Pressure loss tube heat exchanger

Exchanger surface 0,5 - 1 m²






Exchanger surface 1,5 - 3 m²



Exchanger surface 5 - 10 m²



Custom water heaters with 1 or 2 inspection holes and tube heat exchanger

The Boil custom range has been designed to give the user the possibility of composing the system for the production of domestic hot water that best suits the project requirements. The selection concerns the type of accumulation, volume and power of the desired exchanger. This makes it possible to create flexible solutions in terms of storage type, volume and power of the exchanger.

BOIL CUSTOM 1 INSPECTION HOLE

This solution makes it possible to couple the domestic hot water storage with a tube bundle or copper spiral exchanger.

BOIL CUSTOM 2 INSPECTION HOLES


This solution makes it possible to couple each of the two hatches of the sanitary water storage. with a tube bundle or copper spiral heat exchanger. It is also possible to install just one exchanger, allocating the remaining hatch to the inspection function: in this case it is necessary to provide a blank closing plate.

❖ HOW TO CONFIGURE BOIL CUSTOM WITH 1 INSPECTION HOLE

1. Select a FLEXY or FLEXY INOX storage tank with 1 hole from the following page
2. Select the suitable exchanger model based on compatibility with the storage tank and the thermal power to be exchanged:
   - Tube bundle (See page 204)
   - Coiled copper coil (See page 206)

❖ HOW TO CONFIGURE BOIL CUSTOM WITH 2 INSPECTION HOLES

1. Select a FLEXY or FLEXY INOX tank with 2 hatches from the following page
2. For each hatch, select the suitable exchanger model based on compatibility with the storage tank and the thermal power to be exchanged:
   - Tube bundle (See page 204)
   - Coiled copper coil (See page 206)
3. Optionally select the blanking plate from the following page





CHECK UPDATED PRICE LIST

go.fiorinigroup.it/pr


Custom water heaters with 1 or 2 inspection holes and tube heat exchanger



	ENAMELLED FLEXY 1 INSPECTION HOLE (PAG 156)				ST. STEEL FLEXY 1 INSPECTION HOLE (PAG 164)			
Cap. l	Code	Price	Energy label	Inspection hole Øext mm	Code	Price	Energy label	Inspection hole Øext mm
200	817060032X		B	Ø300	817040188X		B	Ø300
300	817060033X		B	Ø300	817040189X		B	Ø300
500	817060034X		C	Ø300	817040190X		C	Ø300
750	817060035X		C	Ø380	817040191X		C	Ø380
1000	817060036X		C	Ø380	817040192X		C	Ø380
1500	817080112X		C	Ø380	817040193X		C	Ø380
2000	817080099X		C	Ø430	817040194X		C	Ø430
2500	817080100X			Ø430	817040195X			Ø430
3000	817080101X			Ø430	817040196X			Ø430
4000	817080102X			Ø430	817040197X			Ø430
5000	817080103X			Ø430	817040198X			Ø430



	ENAMELLED FLEXY 2 INSPECTION HOLES (PAG 164)				ST. STEEL FLEXY 2 INSPECTION HOLES (PAG 166)			
Cap. l	Code	Price	Energy label	Inspection hole Øext mm	Code	Price	Energy label	Inspection hole Øext mm
200	817080134X		B	Ø300	817040199X		B	Ø300
300	817080135X		B	Ø300	817040200X		B	Ø300
500	817080136X		C	Ø300	817040201X		C	Ø300
750	817080191X		C	Ø380	817040202X		C	Ø380
1000	817080138X		C	Ø380	817040203X		C	Ø380
1500	817080139X		C	Ø380	817040204X		C	Ø380
2000	817080140X		C	Ø430	817040205X		C	Ø430
2500	817080141X			Ø430	817040206X			Ø430
3000	817080142X			Ø430	817040207X			Ø430
4000	817080143X			Ø430	817040208X			Ø430
5000	817080144X			Ø430	817040209X			Ø430



		Enamelled heads		Stainless steel heads	
Diametre mm	Tank capacity	Code	Price	Code	Price
Ø300	from 200 to 500 l	843030018X		843040019X	
Ø380	from 750 to 1500 l	843030019X		843040020X	
Ø430	from 2000 to5000 l	843030020X		843040021X	


The heads are supplied complete with bolts and gasket.

CHECK UPDATED PRICE LIST


go.fiorinigroup.it/pr

Bundle tube heat exchanger

Water only





Steam only



Couplings legend

D	Drain
N1	Exchanger inlet/outlet
N2	Exchanger inlet/outlet
T	Vent
1	Gasket without cross-beam
2	Bundle tube heat exchangers
3	Gasket with cross-beam
4	Head





Technical information tube heat exchanger

Surf. m²	Power* kW	Lt mm	Øext mm	Øhe mm	N1 inch	N2 inch	T, D inch	Z1 mm	Z2 mm	n° holes	Vol. l	dp mca
0,5	12,2	460	300	166	1"	1"	3/8"	120	262	16	1,84	0,65
0,75	18,4	445	300	202	1"	1"	3/8"	120	262	16	2,44	0,65
1	24,5	475	300	202	1"	1"	3/8"	120	262	16	3,23	0,7
1,5	36,7	600	380	270	2"	2"	3/8"	145	345	19	5,36	0,75
2	49	600	380	270	2"	2"	3/8"	145	345	19	6,51	0,8
3	73,5	720	380	278	2"	2"	3/8"	145	345	19	9,8	0,9
4	98	750	430	316	2"	2"	3/8"	190	395	22	13,2	1
5	122,5	780	430	324	2"	2"	3/8"	190	395	22	16,68	1,1
6	147	895	430	324	2"	2"	3/8"	190	395	22	19,2	1,2
8	196	1250	430	324	2"	2"	3/8"	190	395	22	27	1,3
10	245	1510	430	324	2"	2"	3/8"	190	395	22	32,7	1,4

Performance calculated with primary 80°C and domestic water 10-45°C

Compatibility between (1) the tube heat exchanger and (4) the storage tank

	Surface m²										
Cap. l	0,5	0,75	1	1,5	2	3	4	5	6	8	10
200	✔	✔	✔								
300	✔	✔	✔								
500	✔	✔	✔								
800				✔	✔	✔					
1000				✔	✔	✔					
1500				✔	✔	✔					
2000							✔	✔	✔		
2500							✔	✔	✔		
3000							✔	✔	✔	✔	
4000							✔	✔	✔	✔	
5000							✔	✔	✔	✔	✔


✔ Combination is possible

	Version 1 Stainless steel AISI 304		Version 2 Stainless steel AISI 316		Version with steam P ≤ 6 bar			Version with steam P ≤ 12 bar		
surf. m²	Code	Price	Code	Price	Code	Price	cat. P.E.D.	Code	Price	cat. P.E.D.
0,5	821030379X		821030393X		821030285X		Art.4 par.3	821030405X		Cat. I
0,75	821030380X		821030394X		821030286X		Art.4 par.3	821030406X		Cat. I
1	821030381X		821030395X		821030287X		Art.4 par.3	821030407X		Cat. I
1,5	821030382X		821030396X		821030288X		Cat. I	821030408X		Cat. I
2	821030383X		821030397X		821030289X		Cat. I	821030409X		Cat. I
3	821030385X		821030399X		821030291X		Cat. I	821030411X		Cat. I
4	821030386X		821030400X		821030292X		Cat. I	821030412X		Cat. II
5	821030387X		821030401X		821030293X		Cat. I	821030413X		Cat. II
6	821030388X		821030402X		821030294X		Cat. I	821030414X		Cat. II
8	821030389X		821030403X		821030296X		Cat. I	821030416X		Cat. II
10	821030390X		821030404X		821030418X		Cat. II	821030418X		Cat. II


Version 1: AISI 304 stainless steel tube heat exchanger, assembled on a varnished plate with galvanised head
Version 2 and version with steam: AISI 306 stainless steel tube heat exchanger on a AISI 316 steel plate and AISI 304 steel head

Bundle tube heat exchanger
Curve: pressure loss


Exchanger surface 0,5 - 1 m²



Exchanger surface 1,5 - 3 m²




Exchanger surface 4 - 10 m²




Copper spiral coil

CHECK UPDATED PRICE LIST

go.fiorinigroup.it/pr





Compatibility chart for copper spiral coil and storage tank

Capacity l	Surface m²							
	0,82	1,38	1,53	2,27	3,1	4,54	5,26	6,34
200	✔	✔	✔					
300	✔	✔	✔					
500	✔	✔	✔	✔	✔			
800	✔	✔	✔	✔	✔	✔	✔	✔
1000	✔	✔	✔	✔	✔	✔	✔	✔
1500	✔	✔	✔	✔	✔	✔	✔	✔
2000	✔	✔	✔	✔	✔	✔	✔	✔
2500	✔	✔	✔	✔	✔	✔	✔	✔
3000	✔	✔	✔	✔	✔	✔	✔	✔
4000	✔	✔	✔	✔	✔	✔	✔	✔
5000	✔	✔	✔	✔	✔	✔	✔	✔

✔ Combination is possible

Couplings legend

N1	Ingresso/uscita scambiatore
N2	Ingresso/uscita scambiatore
1	Guarnizione S/T (senza traverso)
2	Serpentino rame alettato
3	Piastra di montaggio

Technical information copper spiral coil


Surf. m²	Lt mm	Øhe mm	Z1 mm	N1 inch	N2 inch	Type of coil	Internal volume l	Dp kPa	Thermal eff. (*) kW	T max °C	P max bar
0,82	380	160	75	3/4"	3/4"	Single coil	0,7	25	15	99	9
1,38	420	170	75	3/4"	3/4"	Single coil	1,2	30	21,6	99	9
1,53	450	170	75	3/4"	3/4"	Single coil	1,4	35	24	99	9
2,27	570	170	75	3/4"	3/4"	Single coil	2	35	27	99	9
3,1	550	180	90	1"1/4	1"1/4	Double coil	2,7	26	35	99	9
4,54	570	242	120	1"1/4	1"1/4	Double coil	3,9	35	55	99	9
5,26	660	242	120	1"1/4	1"1/4	Double coil	4,5	35	57,5	99	9
6,34	780	242	120	1"1/4	1"1/4	Double coil	5,5	35	61,5	99	9

*Performance calculated with the following temperatures: primary 80°C and domestic water 10-45°C

Surface area m²	Assembled on a plate Ø300		Assembled on a plate Ø380		Assembled on a plate Ø430	
	Code	Price	Code	Price	Code	Price
0,82	821040017		821040254X		821040259X	
1,38	821040019		821040255X		821040260X	
1,53	821040020		821040256X		821040261X	
2,27	821040252X		821040021		821040262X	
3,1	821040253X		821040022		821040263X	
4,54	-		821040023		821040027	
5,26	-		821040257X		821040024	
6,34	-		821040258X		821040025	

The copper coils are supplied with plates, bolts, nuts and gaskets

Copper spiral coil
Curve: pressure loss





Download additional content

go.fiorinigroup.it/eng/content

fiorini

Fiorini Industries S.r.l.
Ph. +39 0543 723197 – Fax +39 0543 720413
Via Zampeschi 119 – 47122 Forlì (FC) – Italy
www.fiorini-industries.com